



DAYLON

Lever

SAFE LOCK

SPECIFICATIONS

ANSI/BHMA	Grade 3 certified
Door prep	Cross Bore 2-1/8", Edge Bore 1"
Backset	Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/8" - 1-3/4" standard doors
Cylinder	Traditional 5-Pin, Pin & Tumbler
Latch	1" x 2-1/4" square-corner or drive in
Strikes	Knob/lever: 2-1/4" full lip, specify round corner
Bolt	Knob/Lever: 1/2" Throw
Door Handling	Non-handed (except 7000 function)
ADA	N/A
UL	Meets UL 3 hour fire rating for all UL functions
Warranty	Lifetime Mechanical & 5 Year-Limited Finish

AVAILABLE FINISHES



11P
Venetian Bronze



15
Satin Nickel



26
Polished Chrome







26D
Satin Chrome



514
Iron Black

FUNCTION AVAILABILITY

Model No. Description (ANSI/BHMA functions are listed in italics)

	1000/1002UL	Passage/Hall/Closet: Both levers always free. -F75
	3000	Privacy/Bed/Bath: Both levers locked or unlocked by turnbutton inside. Outside knob unlocked by emergency key. -F76
	5000	Entry: Both levers locked or unlocked by key outside or turnbutton inside. -F82
	7000	Half Dummy Trim, Surface Mounted: For doors where only a pull is required. No operation. -Int.

SAFE LOCK

weiserlock.com